

The distinct difference.



## **Specifications**

- JAM style
- 30mm stroke
- 135.79mm shut height
- 5-22mm terminal pitch max
- Less than 30mm terminal length max
- Side feed
- Applicable terminal thickness is 0.6 mm max
- Overall dimensions 82(L)X172(W)X162 mm
- Weighs 5kg approx.
- Pre-feed feeding method

<sup>\*</sup>Specifications may vary depending on terminals size etc.






## **Features**

- Robust in design
- Applicable for miniature terminals
- Crimp height can be adjustable up to 10 microns
- Long lasting tool life
- Suits on both Automatic and Bench top Machine

JAM applicators, recognized as global standard, have evolved constantly over decades of know-how and focus on precision and accuracy. Our applicators are designed to suit wide range of terminals made by JAM as well as other terminal manufacturers. As a 'Machine & Connector' company with long standing experience in manufacturing wide range of wire processing equipment, we understand the critical and varied 'crimp' requirements of customers. Our applicators are manufactured using high grade material, encompassing the synthesis of technological prowess, know-how and spirit of Japanese 'monozukuri' manufacturing practices.



17 & 18, 2<sup>nd</sup> floor 7<sup>th</sup> main, Nanjappa Garden, Kalyan Nagar, Bengaluru. India. 560043. Email: - jamind@jamind.in

